

IR FIXED LENS VANDAL-PROOF DOME CAMERA

DAI-380IP04



Sony Exmor IMX138 1/3" CMOS
1.3 Mega-Pixel
True Day & Night (IR Cut Removable)
0 Lux (IR On) Min. Illumination
ONVIF

Digital WDR
3D Noise Reduction
BLC/HLC
Motion Detection and Privacy Masking
4mm Mega-Pixel Lens



30m IR Illumination
PoE Support
1 Way Audio
IP 66 Protection
Vandal-Proof

Specifications

Camera	Video	Model	DAI-380IP04
		Image Sensor	Sony Exmor IMX138 1/3" CMOS
		Effective Pixels	1280x1025
		Electronic Shutter	1/25s ~ 1/100000s
		Day & Night	ICR
		Min. Illumination	0lux (IR ON)
	Audio	Audio compression	G711A
		Communication	One Way Audio
	Image Enhancement	Image Settings	AWB, AES, AGC Adjustable Exposure Mode (Auto / Manual) BLC, HLC Adjustable Sharpness, Saturation, Brightness & Contrast Adjustable
		WDR Range	Digital WDR
		Noise Reduction	3D-DNR
		Image Orientation	Mirror/Flip
		Privacy Zone	Yes
		Motion Detection	Yes
		Compression	Video Compression
Resolution	960P (1280x960), 720P (1280x720), VGA (640x480), QVGA (320x240)		
Multi-stream	"1280x960 (1~30fps) / 1280x720 (1~30fps) / 1280x720 (1~30fps) / 640x480 (1~30fps) / 320x240 (1~30fps)"		
Bit rate	64Kbps ~ 4Mbps		
Encode Mode	VBR/CBR		
Image Quality	Five levels under VBR; Free adjustment under CBR		

Housing	IR Distance	15m (24 IR LED)
	Lens	4mm
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Water-proof	IP66
	Bracket	3-Axis Gimbal
	Dimensions	Φ116mm×91mm
Connectivity	Weight(gross)	605g
	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	CVBS (BNCx1)
	Mic Connectivity	1Ch Input
	SD Card	No
	RS485	No
Network	Alarm	No
	Remote Monitoring	IE Browsing, CMS 2.0 Control Software
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
	ONVIF	Yes, GB-T/28181-2012
	Ethernet	100Mbps
	PoE	Yes
Others	Power Supply	DC12V/PoE
	Work Environment	-10℃ ~50℃, 10%~90% Humidity

